

Data Sheet

AGRICULTURE

February 2019

TRIMBLE RESELLER CONFIDENTIAL

TMX-2050/XCN-2050 Display Data Sheet

Technical	
Power	27 volts, 3.5 amps (supplied by the TM-200 Module)
Processor (CPU)	1 GHz quad core
Storage	Primary embedded memory - 32 GB
Mechanical	
Dimensions	312 mm x 214 mm x 45 mm (plus connectors) (1 ft 8/32 in x 8 ¼ in x 1 49/64 in)
Weight	2.5 kg (5.5 lb)
Mount	4 M6 screws on 75 mm centers (3 inch). VESA MIS-D 75.
Housing	
Material	Magnesium
Environmental Rating	IP55
Temperature	
Operation	0 °C to 65 °C (32 °F to 149 °F)
Storage	-40 °C to 85 °C (-40 °F to 185 °F)
LCD Display	
Size	307 mm (1 ft 3/32 in)
Touch Screen	Capacitive touch
Resolution	1280 x 800
Front-Facing Camera	
Type	Low light level, color
Resolution	1.3 M pixels
Connections	
USB	USB side (side of display), USB rear (back of display)
Ethernet	RJ45 connector. Power input for Precision-IQ only.

For More Information

Contact your local Trimble Regional Sales Manager.

<http://agpartners.trimble.com>

www.trimble.com

© 2019, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo are trademarks of Trimble Trimble Inc., registered in the United States and in other countries. Precision-IQ is a trademark/trademarks of Trimble Inc. All other trademarks are the property of their respective owners.